

# STRAIGHT COUPLINGS SELECTION CHART

NOM. PIPE SIZE DN	DACL		STEEL		ECOUPUR	CICL		AC		ABS*1	GRP*2	RC	COPPER	PVC-U/M*4	
	AS/NZS 2280	MSCL AS 1579	GWI AS 1074	CLASS C&K EN 545:2010 EN 545:2007	CLASS B AS 1724	CLASS C AS 2544	CLASS AB AS 1711	CLASS CD AS 1711	SERIES 1 AS 3518	SERIES 1 AS 3571	AS 4058	AS 1432	SERIES 1 (U) AS/NZS 1477 (M) AS/NZS 4765	SERIES 2 (U) AS/NZS 1477 (M) AS/NZS 4765 (O) AS/NZS 4441	
40			60150059xx?? 48mm						60150059xx?? 48mm			N/A 38mm	60150059xx?? 48mm		
50			60150071xx?? 60mm				6015071xx?? 69mm		601500071xx?? 60mm			60150059xx?? 51mm	60150071xx?? 60mm		
65			60150084xx?? 76mm				60150084xx?? 79mm		601500084xx?? 75mm			60150071xx?? 64mm	60150084xx?? 75mm		
80	60150103xx?? 96mm		60150103xx?? 89mm		60150103xx?? 96mm	60150103xx?? 96mm	60150103xx?? 96mm	60150103xx?? 96mm	60150103xx?? 89mm			60150084xx?? 76mm	60150103xx?? 89mm		
100	60150133xx?? 122mm	60150133xx?? 114mm	60150133xx?? 114mm	60150133xx?? 118mm	60150133xx?? 122mm	60150133xx?? 122mm	60150133xx?? 122mm	60150133xx?? 122mm	60150133xx?? 114mm	60150133xx?? 122mm		60150103xx?? 101mm	60150133xx?? 114mm	60150133xx?? 122mm	
125		60150147xx?? 140mm	60150147xx?? 140mm	60150147xx?? 144mm					60150147xx?? 140mm			60150147xx?? 127mm	60150147xx?? 140mm		
150	60150182xx?? 60150194xx?? 177mm	60150182xx?? 168mm	60150182xx?? 165mm	60150182xx?? 170mm	60150182xx?? 60150194xx?? 177mm	60150182xx?? 60150194xx?? 177mm	60150182xx?? 60150194xx?? 177mm	60150182xx?? 60150194xx?? 177mm	60150182xx?? 168mm	60150182xx?? 60150194xx?? 177mm	60150202xx?? 197mm	N/A 152mm	60150182xx?? 160mm	60150182xx?? 60150194xx?? 177mm	
175														60150202xx?? 200mm	
200	60150238xx?? 232mm	60150238xx?? 219mm		60150238xx?? 222mm	60150238xx?? 232mm	60150238xx?? 232mm	60150238xx?? 232mm	60150238xx?? 232mm	60150238xx?? 225mm	60150238xx?? 232mm		N/A 203mm	60150238xx?? 225mm	60150238xx?? 232mm	
225	60150264xx?? 259mm	60150264xx?? 257mm			60150264xx?? 259mm	60150264xx?? 259mm	60150264xx?? 259mm	60150264xx?? 259mm	60150264xx?? 250mm	60150264xx?? 259mm	60150296xx?? 279mm	60150238xx?? 229mm	60150264xx?? 250mm	60150264xx?? 259mm	
250	60150296xx?? 286mm	60150296xx?? 273mm		60150296xx?? 274mm	60150296xx?? 286mm	60150296xx?? 286mm	60150296xx?? 286mm	60150296xx?? 286mm		60150296xx?? 286mm			60150296xx?? 280mm	60150296xx?? 286mm	
300	60150354xx?? 345mm	60150334xx?? 324mm		60150334xx?? 326mm	60150354xx?? 334mm	60150354xx?? 345mm	60150354xx?? 334mm	60150354xx?? 345mm	60150334xx?? 315mm	60150354xx?? 345mm	60150370171 362mm		60150334xx?? 315mm	60150354xx?? 345mm	
350		60150370171 355mm							60150370171 355mm	60150420171 399mm			60150370171 355mm		
375	60150434171 426mm	60150420171 406mm		60150384171 377mm	60150434171 413mm	60150434171 426mm	60150434171 413mm	60150434171 426mm	60150420171 400mm	60150434171 453mm	60150460171 445mm		60150420171 400mm	60150434171 426mm	
400		60150460171 60150468171 457mm		60150446171 429mm					60150460171 60150468171 450mm	60150468171 453mm			60150460171 60150468171 450mm		
450	60150512171 60150522171 507mm	60150512171 60150522171 508mm		60150490171 480mm	60150512171 492mm	60150512171 60150522171 507mm	60150512171 60150522171 507mm	60150512171 60150522171 507mm	60150512171 500mm	60150512171 60150522171 507mm	60150546171 533mm		60150512171 60150522171 500mm	60150512171 60150522171 507mm	
500	60150566171 60150576171 560mm	60150566171 60150576171 559mm		60150546171 532mm	60150554171 545mm	60150566171 60150576171 560mm			60150566171 60150576171 560mm	60150566171 60150576171 560mm			60150566171 60150576171 560mm	60150566171 60150576171 560mm	
525		60150620171 610mm					60150576171 60150584171 572mm	60150598171 587mm		60150598171 587mm	60150626171 616mm				
600	60150672171 60150682171 667mm	60150672171 60150682171 660mm		60150644171 635mm	60150654171 60150672171 650mm	60150672171 60150682171 667mm	60150654171 60150672171 650mm	60150672171 60150682171 667mm	60150654171 630mm	60150672171 60150682171 667mm	60150714171 699mm		60150644171 630mm	60150672171 60150682171 667mm	

Note: The AVK Supa-Gib Coupling range extends beyond DN600. For sizes and configurations not listed above, please contact AVK for assistance.

\*1 Min. required pipe rating for coupling application: PN9 | \*2 Min. required pipe rating for coupling application: SN5,000 | \*3 Min. required pipe rating for clamp coupling application: U=PN9 / M=PN12 / O=PN16 | \*4 xx = Sleeve material | \*5 ?? = Bracket material & fasteners

## Couplings typical specifying sequence table - 601501331501

601	5	0133	15	0	1
AVK Series Straight Coupling					
Wangaratta					
Maximum Dia - 0059 through to 1314					
Sleeve material = xx 11 = 316SS 110mm long 15 = 316SS 176mm long 21 = DI 110mm long	13 = 316SS 136mm long 17 = 316SS 216mm long 25 = DI 176mm long				
Bracket material = ?	0 = Cast DI	1 = 316SS			
Fasteners = ?	0 = 316SS	1 = GAL			



**AVK Wang Pty Ltd**  
Cnr Sandford Road & Gibson Street  
Wangaratta, VIC 3677  
Australia  
T: +61 8 8368 0900  
F: +61 8 8368 0970  
E: enquiries@avkau.com.au  
W: www.avkcivil.com.au

Expect... **AVR**