



STANDARDSMARK LICENCE

SAI Global hereby grants:

AVK Australia Holding Pty Ltd

ABN 11 081 236 777

559A Grand Junction Road, Wingfield, SA 5013, Australia

StandardsMark Licence

Manufactured to:

**AS/NZS 2638.2:2011 - Gate valves for waterworks purposes - Resilient seated
& AS/NZS 2638.1:2011 - Gate valves for waterworks purposes - Metal seated**

"the StandardsMark Licensee" the right to use the STANDARDSMARK as shown below only in respect of the goods described and detailed in the Schedule which are produced by the Licensee or on behalf of the Licensee* and which comply with the appropriate Standard referred to above as from time to time amended. The Licence is granted subject to the rules governing the use of the STANDARDSMARK and the Terms and Conditions for certification and licence. The Licensee covenants to comply with all the Rules and Terms and Conditions.

Licence No: SMK02420

Issued : 23 January 2021

Expires : 9 December 2024

Originally Certified : 9 May 2000

Current Certification : 22 January 2021

Frank Camatsa
Global Head of Technical Services
SAI Global Assurance



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to www.saiglobal.com, for the list of product models.



SCHEDULE TO STANDARDSMARK LICENCE

SAI Global hereby grants:

AVK Australia Holding Pty Ltd

559A Grand Junction Road, Wingfield, SA 5013, Australia

StandardsMark Licence

Manufactured to:

AS/NZS 2638.1:2011 - Gate valves for waterworks purposes - Metal seated

Model identification of the goods on which the STANDARDSMARK may be used:

| Model Identification | Brand Name | Nominal Size | Product Description | Product Type | Valve class (Allowable operating Pressure) | Max Operating Temperature | End Connection Designation | Date Endorsed |
|-------------------------|------------|--------------|----------------------------------------------------------------------------------------------------------|-------------------------|--------------------------------------------------|------------------------------|-------------------------------|---------------|
| 2580/8X -DN080 | Sureflow | DN080 | 2580 series Polymeric coated Metal Seated Gate Option Y = 0 (Stem Cap) Y = 2 (Gearbox) Y = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN80 Flange x DN80 Flange | 21 Jan 2021 |
| 2580/8X -DN100 | Sureflow | DN100 | 2580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN100 Flange x DN100 Flange | 21 Jan 2021 |
| 2580/8X -DN225 | Sureflow | DN225 | 2580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN225 Flange x DN225 Flange | 21 Jan 2021 |
| 2580/8X -DN250 | Sureflow | DN250 | 2580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN250 Flange x DN250 Flange | 21 Jan 2021 |
| 2580/8X -DN300 | Sureflow | DN300 | 2580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN300 Flange x DN300 Flange | 21 Jan 2021 |
| 580/8X -DN080 | AVK | DN080 | 580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN80 Flange x DN80 Flange | 21 Jan 2021 |
| 580/8X -DN100 | AVK | DN100 | 580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN100 Flange x DN100 Flange | 21 Jan 2021 |
| 580/8X -DN150 | AVK | DN150 | 580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN150 Flange x DN150 Flange | 21 Jan 2021 |
| 580/8X -DN200 | AVK | DN200 | 580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN200 Flange x DN200 Flange | 21 Jan 2021 |
| 580/8X -DN225 | AVK | DN225 | 580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN225 Flange x DN225 Flange | 21 Jan 2021 |
| 580/8X -DN250 | AVK | DN250 | 580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN250 Flange x DN250 Flange | 21 Jan 2021 |
| 580/8X -DN300 | AVK | DN300 | 580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN300 Flange x DN300 Flange | 21 Jan 2021 |
| 2580/8X -DN150 | Sureflow | DN150 | 2580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN150 Flange x DN150 Flange | 21 Jan 2021 |
| 2580/8X -DN200 | Sureflow | DN200 | 2580 series Polymeric coated Metal Seated Gate Option X = 0 (Stem Cap) X = 2 (Gearbox) X = 8 (Handwheel) | Metal Seated Gate Valve | PN35 | 40°C | DN200 Flange x DN200 Flange | 21 Jan 2021 |
| 2580/90 2580/92 2580/98 | Sureflow | DN 225 | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 2580/90 2580/92 2580/98 | Sureflow | DN 250 | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 2580/90 2580/92 2580/98 | Sureflow | DN 300 | DN300 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 2580/90 2580/92 2580/98 | Sureflow | DN 200 | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 2580/90 2580/92 2580/98 | Sureflow | DN 080 | DN080 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 2580/90 2580/92 2580/98 | Sureflow | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Brand Name | Nominal Size | Product Description | Product Type | Valve class (Allowable operating Pressure) | Max Operating Temperature | End Connection Designation | Date Endorsed |
|----------------------------|------------|--------------|----------------------------------------------------|----------------------------|--------------------------------------------------|------------------------------|-------------------------------|---------------|
| 2580/90 2580/92 2580/98 | Sureflow | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 580/90 580/92 580/98 | AVK | DN 225 | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 580/90 580/92 580/98 | AVK | DN 250 | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 580/90 580/92 580/98 | AVK | DN 300 | DN300 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 580/90 580/92 580/98 | AVK | DN 200 | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 580/90 580/92 580/98 | AVK | DN 080 | DN080 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 580/90 580/92 580/98 | AVK | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| 580/90 580/92 580/98 | AVK | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 70°C | Flange x Flange | 17 Jul 2019 |
| A0412/2-039 DN100 | AVK | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| A0412/2-040 DN150 | AVK | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| A0412/2-041 DN200 | AVK | DN 200 | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| A0412/2-042 DN225 | AVK | DN 225 | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| A0412/2-043 DN250 | AVK | DN 250 | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| A0412/2-044 DN100 | AVK | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Spigot x Spigot | 12 Feb 2019 |
| A0412/2-045 DN150 | AVK | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Spigot x Spigot | 12 Feb 2019 |
| A0412/2-046 DN80 | AVK | DN 80 | DN80 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-047 DN100 | AVK | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-048 DN150 | AVK | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-049 DN200 | AVK | DN 200 | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-050 DN225 | AVK | DN 225 | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-051 DN250 | AVK | DN 250 | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-052 DN300 | AVK | DN 300 | DN300 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-053 DN375 | AVK | DN 375 | DN375 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-054 DN450 | AVK | DN 450 | DN450 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-055 DN500 | AVK | DN 500 | DN500 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-056 DN600 | AVK | DN 600 | DN600 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-057 DN750 | AVK | DN 750 | DN750 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-065 DN80 | AVK | DN 80 | DN80 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-066 DN100 | AVK | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-067 DN150 | AVK | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-068 DN200 | AVK | DN 200 | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-069 DN225 | AVK | DN 225 | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-070 DN250 | AVK | DN 250 | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-071 DN300 | AVK | DN 300 | DN300 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-072 DN375 | AVK | DN 375 | DN375 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-073 DN450 | AVK | DN 450 | DN450 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-074 DN500 | AVK | DN 500 | DN500 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-075 DN600 | AVK | DN 600 | DN600 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-076 DN750 | AVK | DN 750 | DN750 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-078 DN100 | AVK | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Victaulic x Victaulic | 12 Feb 2019 |
| A0412/2-079 DN150 | AVK | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Victaulic x Victaulic | 12 Feb 2019 |
| A0412/2-095 DN375 | AVK | DN 375 | DN375 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-096 DN375 | AVK | DN 375 | DN375 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-097 DN500 | AVK | DN 500 | DN500 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-098 DN500 | AVK | DN 500 | DN500 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Brand Name | Nominal Size | Product Description | Product Type | Valve class (Allowable operating Pressure) | Max Operating Temperature | End Connection Designation | Date Endorsed |
|----------------------|------------|--------------|-------------------------------------------------|-------------------------|--------------------------------------------------|------------------------------|-------------------------------|---------------|
| A0412/2-099 DN600 | AVK | DN 600 | DN600 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-100 DN600 | AVK | DN 600 | DN600 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-101 DN750 | AVK | DN 750 | DN750 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-102 DN750 | AVK | DN 750 | DN750 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-103 DN450 | AVK | DN 450 | DN450 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-104 DN450 | AVK | DN 450 | DN450 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-109 DN900 | AVK | DN 900 | DN900 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-112 DN900 | AVK | DN 900 | DN900 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-115 DN900 | AVK | DN 900 | DN900 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| A0412/2-116 DN900 | AVK | DN 900 | DN900 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-039 DN100 | Sureflow | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| S0412/2-040 DN150 | Sureflow | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| S0412/2-041 DN200 | Sureflow | DN 200 | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| S0412/2-042 DN225 | Sureflow | DN 225 | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| S0412/2-043 DN250 | Sureflow | DN 250 | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Socket x Socket | 12 Feb 2019 |
| S0412/2-044 DN100 | Sureflow | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Spigot x Spigot | 12 Feb 2019 |
| S0412/2-045 DN150 | Sureflow | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Spigot x Spigot | 12 Feb 2019 |
| S0412/2-046 DN80 | Sureflow | DN 80 | DN80 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-047 DN100 | Sureflow | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-048 DN150 | Sureflow | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-049 DN200 | Sureflow | DN 200 | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-050 DN225 | Sureflow | DN 225 | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-051 DN250 | Sureflow | DN 250 | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-052 DN300 | Sureflow | DN 300 | DN300 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-053 DN375 | Sureflow | DN 375 | DN375 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-054 DN450 | Sureflow | DN 450 | DN450 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-055 DN500 | Sureflow | DN 500 | DN500 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-056 DN600 | Sureflow | DN 600 | DN600 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-057 DN750 | Sureflow | DN 750 | DN750 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-065 DN80 | Sureflow | DN 80 | DN80 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-066 DN100 | Sureflow | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-067 DN150 | Sureflow | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-068 DN200 | Sureflow | DN 200 | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-069 DN225 | Sureflow | DN 225 | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-070 DN250 | Sureflow | DN 250 | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-071 DN300 | Sureflow | DN 300 | DN300 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-072 DN375 | Sureflow | DN 375 | DN375 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-073 DN450 | Sureflow | DN 450 | DN450 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-074 DN500 | Sureflow | DN 500 | DN500 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-075 DN600 | Sureflow | DN 600 | DN600 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-076 DN750 | Sureflow | DN 750 | DN750 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-078 DN100 | Sureflow | DN 100 | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Victaulic x Victaulic | 12 Feb 2019 |
| S0412/2-079 DN150 | Sureflow | DN 150 | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Victaulic x Victaulic | 12 Feb 2019 |
| S0412/2-095 DN375 | Sureflow | DN 375 | DN375 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-096 DN375 | Sureflow | DN 375 | DN375 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Brand Name | Nominal Size | Product Description | Product Type | Valve class (Allowable operating Pressure) | Max Operating Temperature | End Connection Designation | Date Endorsed |
|----------------------|------------|--------------|-------------------------------------------------------------|-------------------------|--------------------------------------------|---------------------------|----------------------------|---------------|
| S0412/2-097 DN500 | Sureflow | DN 500 | DN500 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-098 DN500 | Sureflow | DN 500 | DN500 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-099 DN600 | Sureflow | DN 600 | DN600 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-100 DN600 | Sureflow | DN 600 | DN600 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-101 DN750 | Sureflow | DN 750 | DN750 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-102 DN750 | Sureflow | DN 750 | DN750 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-103 DN450 | Sureflow | DN 450 | DN450 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-104 DN450 | Sureflow | DN 450 | DN450 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-109 DN900 | Sureflow | DN 900 | DN900 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-112 DN900 | Sureflow | DN 900 | DN900 Metal Seated Gate Valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-115 DN900 | Sureflow | DN 900 | DN900 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 12 Feb 2019 |
| S0412/2-116 DN900 | Sureflow | DN 900 | DN900 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35 | 40°C | Flange x Flange | 12 Feb 2019 |
| S2580/92-375 | Sureflow | DN 375 | S2580 DN375 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S2580/92-450 | Sureflow | DN 450 | S2580 DN450 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S2580/92-500 | Sureflow | DN 500 | S2580 DN500 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S2580/92-600 | Sureflow | DN 600 | S2580 DN600 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S2580/93-375 | Sureflow | DN 375 | S2580 DN375 Metal Seated Gate Valve With DN100 Bypass | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S2580/93-450 | Sureflow | DN 450 | S2580 DN450 Metal Seated Gate Valve With DN100 Bypass | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange Bypass | 21 Aug 2020 |
| S2580/93-500 | Sureflow | DN 500 | S2580 DN500 Metal Seated Gate Valve With DN150 Bypass | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange Bypass | 21 Aug 2020 |
| S2580/93-600 | Sureflow | DN 600 | S2580 DN600 Metal Seated Gate Valve with DN150 Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange Bypass | 21 Aug 2020 |
| S580/92-375 | AVK | DN 375 | S580 DN375 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S580/92-450 | AVK | DN 450 | S580 DN450 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S580/92-500 | AVK | DN 500 | S580 DN500 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S580/92-600 | AVK | DN 600 | S580 DN600 Metal Seated Gate Valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S580/93-375 | AVK | DN 375 | S580 DN375 Metal Seated Gate Valve With DN100 Bypass | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange | 21 Aug 2020 |
| S580/93-450 | AVK | DN 450 | S580 DN450 Metal Seated Gate Valve With DN100 Bypass | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange Bypass | 21 Aug 2020 |
| S580/93-500 | AVK | DN 500 | S580 DN500 Metal Seated Gate Valve With DN150 Bypass | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange Bypass | 21 Aug 2020 |
| S580/93-600 | AVK | DN 600 | S580 DN600 Metal Seated Gate Valve with DN150 Bypass valve | Metal Seated Gate Valve | 16 | 40°C | Flange x Flange Bypass | 21 Aug 2020 |

AS/NZS 2638.2:2011 - Gate valves for waterworks purposes - Resilient seated

Model identification of the goods on which the STANDARDSMARK may be used:

| Model Identification | Model Name | Brand Name | Product Description | Product Type | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|------------------------|-------------------------------------------|----------------------------|----------------------------|---------------|
| 2055/74 | RSGV | Sureflow | DN500 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 500 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Aug 2017 |
| 2055/74 | RSGV | Sureflow | DN450 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 450 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Aug 2017 |
| 2055/74 | RSGV | Sureflow | DN600 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 600 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Aug 2017 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICEISE

| Model Identification | Model Name | Brand Name | Product Description | Product Type | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|------------------------|-------------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 2055/80 | RSGV | Sureflow | DN600 Resilient Seated Gate Valve with DN150 Bypass valve | Resilient Seated Gate Valve | DN 600 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Aug 2017 |
| 2570/50 | RSGV | Sureflow | DN375 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 375 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 2570/50 | RSGV | Sureflow | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 2570/50 | RSGV | Sureflow | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 2570/50 | RSGV | Sureflow | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 2570/50 | RSGV | Sureflow | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 2570/50 | RSGV | Sureflow | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 2570/50 | RSGV | Sureflow | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 2570/50 | RSGV | Sureflow | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 2570/60 | RSGV | Sureflow | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/60] 2/Handwheel [2570/68] 3/Gearbox [2570/62] | Option of CC or ACC | Spigot x Spigot | 22 Mar 2019 |
| 2570/60 | RSGV | Sureflow | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/60] 2/Handwheel [2570/68] 3/Gearbox [2570/62] | Option of CC or ACC | Spigot x Spigot | 22 Mar 2019 |
| 2570/60 | RSGV | Sureflow | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/60] 2/Handwheel [2570/68] 3/Gearbox [2570/62] | Option of CC or ACC | Spigot x Spigot | 22 Mar 2019 |
| 2570/60 | RSGV | Sureflow | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN080 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/60] 2/Handwheel [2570/68] 3/Gearbox [2570/62] | Option of CC or ACC | Spigot x Spigot | 22 Mar 2019 |
| 2570/60 | RSGV | Sureflow | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/60] 2/Handwheel [2570/68] 3/Gearbox [2570/62] | Option of CC or ACC | Spigot x Spigot | 1 Aug 2017 |
| 2570/60 | RSGV | Sureflow | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/60] 2/Handwheel [2570/68] 3/Gearbox [2570/62] | Option of CC or ACC | Spigot x Spigot | 1 Aug 2017 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description | Product Type | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|------------------------|-------------------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 2570/60 | RSGV | Sureflow | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/60] 2/Handwheel [2570/98] 3/Gearbox [2570/62] | Option of CC or ACC | Spigot x Spigot | 1 Aug 2017 |
| 2570/70 | RSGV | Sureflow | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/70] 2/Handwheel [2570/78] 3/Gearbox [2570/72] | Option of CC or ACC | Flange x Socket | 1 Aug 2017 |
| 2570/70 | RSGV | Sureflow | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/70] 2/Handwheel [2570/78] 3/Gearbox [2570/72] | Option of CC or ACC | Flange x Socket | 1 Aug 2017 |
| 2570/70 | RSGV | Sureflow | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/70] 2/Handwheel [2570/78] 3/Gearbox [2570/72] | Option of CC or ACC | Flange x Socket | 1 Aug 2017 |
| 2570/90 | RSGV | Sureflow | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/90] 2/Handwheel [2570/98] 3/Gearbox [2570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 2570/90 | RSGV | Sureflow | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/90] 2/Handwheel [2570/98] 3/Gearbox [2570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 2570/90 | RSGV | Sureflow | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/90] 2/Handwheel [2570/98] 3/Gearbox [2570/92] | Option of CC or ACC | Flange x Flange | 28 Feb 2017 |
| 2570/90 | RSGV | Sureflow | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/90] 2/Handwheel [2570/98] 3/Gearbox [2570/92] | Option of CC or ACC | Flange x Flange | 28 Feb 2017 |
| 2570/90 | RSGV | Sureflow | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/90] 2/Handwheel [2570/98] 3/Gearbox [2570/92] | Option of CC or ACC | Flange x Flange | 28 Feb 2017 |
| 2570/90 | RSGV | Sureflow | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/90] 2/Handwheel [2570/98] 3/Gearbox [2570/92] | Option of CC or ACC | Flange x Flange | 28 Feb 2017 |
| 2570/90 | RSGV | Sureflow | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/90] 2/Handwheel [2570/98] 3/Gearbox [2570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 2570/90 | RSGV | Sureflow | DN400 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 400 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/90] 2/Handwheel [2570/98] 3/Gearbox [2570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 2570/90 | RSGV | Sureflow | DN375 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 375 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [2570/90] 2/Handwheel [2570/98] 3/Gearbox [2570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 2570/96 | RSGV | Sureflow | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [2570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 2570/96 | RSGV | Sureflow | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [2570/96] | Option of CC or ACC | FlangexFlange OS&Y | 20 Feb 2019 |
| 2570/96 | RSGV | Sureflow | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [2570/96] | Option of CC or ACC | FlangexFlange OS&Y | 20 Feb 2019 |
| 2570/96 | RSGV | Sureflow | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [2570/96] | Option of CC or ACC | FlangexFlange OS&Y | 20 Feb 2019 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description | Product Type | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|-------------------------------------------|----------------------------|----------------------------|---------------|
| 2570/96 | RSGV | Sureflow | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 080 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [2570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 2570/96 | RSGV | Sureflow | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [2570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 2570/96 | RSGV | Sureflow | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [2570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 55/74 | RSGV | AVK | DN600 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 600 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Aug 2017 |
| 55/74 | RSGV | AVK | DN450 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 450 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Aug 2017 |
| 55/74 | RSGV | AVK | DN500 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 500 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Aug 2017 |
| 55/80 | RSGV | AVK | DN600 Resilient Seated Gate Valve with DN150 Bypass valve | Resilient Seated Gate Valve | DN 600 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Aug 2017 |
| 57 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57 | RSGV | AVK | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57 | RSGV | AVK | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57 | RSGV | AVK | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57 | RSGV | AVK | DN80 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57 | RSGV | AVK | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description | Product Type | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|-------------------------------------------|----------------------------|----------------------------|---------------|
| 57 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57 | RSGV | AVK | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57 | RSGV | AVK | DN375 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 375 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57 | RSGV | AVK | DN400 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 400 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57 | RSGV | AVK | DN80 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Spigot x Spigot | 14 Oct 2011 |
| 57 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Socket | 14 Oct 2011 |
| 57 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Spigot x Spigot | 14 Oct 2011 |
| 57 | RSGV | AVK | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Socket | 14 Oct 2011 |
| 57 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Spigot x Spigot | 14 Oct 2011 |
| 57/55 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description | Product Type | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|---------------------------------|----------------------------|----------------------------|---------------|
| 57/55 | RSGV | AVK | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57/55 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57/55 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57/55 | RSGV | AVK | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57/55 | RSGV | AVK | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57/55 | RSGV | AVK | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Socket x Socket | 14 Oct 2011 |
| 57/65 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Spigot x Spigot | 14 Oct 2011 |
| 57/75 | RSGV | AVK | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Flange x Socket | 14 Oct 2011 |
| 57/90 | RSGV | AVK | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57/90 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57/90 | RSGV | AVK | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57/90 | RSGV | AVK | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 57/90 | RSGV | AVK | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description | Product Type | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 57/90 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HUF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| 570/50 | RSGV | AVK | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 570/50 | RSGV | AVK | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 570/50 | RSGV | AVK | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 570/50 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 570/50 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 570/50 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 570/50 | RSGV | AVK | DN375 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 375 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 570/50 | RSGV | AVK | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC | Socket x Socket | 1 Aug 2017 |
| 570/60 | RSGV | AVK | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN080 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/60] 2/Handwheel [570/68] 3/Gearbox [570/62] | Option of CC or ACC | Spigot x Spigo | 22 Mar 2019 |
| 570/60 | RSGV | AVK | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/60] 2/Handwheel [570/68] 3/Gearbox [570/62] | Option of CC or ACC | Spigot x Spigo | 22 Mar 2019 |
| 570/60 | RSGV | AVK | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/60] 2/Handwheel [570/68] 3/Gearbox [570/62] | Option of CC or ACC | Spigot x Spigo | 22 Mar 2019 |
| 570/60 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/60] 2/Handwheel [570/68] 3/Gearbox [570/62] | Option of CC or ACC | Spigot x Spigot | 1 Aug 2017 |
| 570/60 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/60] 2/Handwheel [570/68] 3/Gearbox [570/62] | Option of CC or ACC | Spigot x Spigot | 1 Aug 2017 |
| 570/60 | RSGV | AVK | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/60] 2/Handwheel [570/68] 3/Gearbox [570/62] | Option of CC or ACC | Spigot x Spigo | 22 Mar 2019 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description | Product Type | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|------------------------|----------------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 570/60 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/60] 2/Handwheel [570/68] 3/Gearbox [570/62] | Option of CC or ACC | Spigot x Spigot | 1 Aug 2017 |
| 570/70 | RSGV | AVK | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/70] 2/Handwheel [570/78] 3/Gearbox [570/72] | Option of CC or ACC | Flange x Socket | 1 Aug 2017 |
| 570/70 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/70] 2/Handwheel [570/78] 3/Gearbox [570/72] | Option of CC or ACC | Flange x Socket | 1 Aug 2017 |
| 570/70 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/70] 2/Handwheel [570/78] 3/Gearbox [570/72] | Option of CC or ACC | Flange x Socket | 1 Aug 2017 |
| 570/90 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/90] 2/Handwheel [570/98] 3/Gearbox [570/92] | Option of CC or ACC | Flange x Flange | 28 Feb 2017 |
| 570/90 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/90] 2/Handwheel [570/98] 3/Gearbox [570/92] | Option of CC or ACC | Flange x Flange | 28 Feb 2017 |
| 570/90 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/90] 2/Handwheel [570/98] 3/Gearbox [570/92] | Option of CC or ACC | Flange x Flange | 28 Feb 2017 |
| 570/90 | RSGV | AVK | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/90] 2/Handwheel [570/98] 3/Gearbox [570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 570/90 | RSGV | AVK | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/90] 2/Handwheel [570/98] 3/Gearbox [570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 570/90 | RSGV | AVK | DN375 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 375 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/90] 2/Handwheel [570/98] 3/Gearbox [570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 570/90 | RSGV | AVK | DN400 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 400 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/90] 2/Handwheel [570/98] 3/Gearbox [570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 570/90 | RSGV | AVK | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/90] 2/Handwheel [570/98] 3/Gearbox [570/92] | Option of CC or ACC | Flange x Flange | 28 Feb 2017 |
| 570/90 | RSGV | AVK | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap [570/90] 2/Handwheel [570/98] 3/Gearbox [570/92] | Option of CC or ACC | Flange x Flange | 10 Apr 2017 |
| 570/96 | RSGV | AVK | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 570/96 | RSGV | AVK | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 570/96 | RSGV | AVK | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 080 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 570/96 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description | Product Type | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|-------------------------------------------|----------------------------|----------------------------|---------------|
| 570/96 | RSGV | AVK | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 570/96 | RSGV | AVK | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 570/96 | RSGV | AVK | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Handwheel [570/96] | Option of CC or ACC | Flange x Flange OS&Y | 20 Feb 2019 |
| 5790 | RSGV | AVK | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100 | 16 | 40°C | Ductile Cast Iron | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC | Flange x Flange | 14 Oct 2011 |
| S2570/42-450 | S2570 | Sureflow | DN450 Resilient Seated Gate Valve With DN100&DN150 Bypass | Resilient Seated Gate Valve | DN 450 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange Bypass | 30 Apr 2020 |
| S2570/42-500 | S2570 | Sureflow | DN500 Resilient Seated Gate Valve With DN100&DN150 Bypass | Resilient Seated Gate Valve | DN 500 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange Bypass | 30 Apr 2020 |
| S2570/42-600 | S2570 | Sureflow | DN600 Resilient Seated Gate Valve With DN100&DN150 Bypass valve | Resilient Seated Gate Valve | DN 600 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange Bypass | 4 May 2020 |
| S2570/42-750 | S2570 | Sureflow | DN750 Resilient Seated Gate Valve With DN150 Bypass | Resilient Seated Gate Valve | DN 750 | 16 | 40°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange Bypass | 1 Oct 2020 |
| S2570/92-450 | S2570 | Sureflow | DN450 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 450 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 30 Apr 2020 |
| S2570/92-500 | S2570 | Sureflow | DN500 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 500 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 30 Apr 2020 |
| S2570/92-600 | S2570 | Sureflow | DN600 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 600 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 30 Apr 2020 |
| S2570/92-750 | S2570 | Sureflow | DN750 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 750 | 16 | 40°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Oct 2020 |
| S570/42-450 | S570 | AVK | DN450 Resilient Seated Gate Valve With DN100&DN150 Bypass | Resilient Seated Gate Valve | DN 450 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange Bypass | 30 Apr 2020 |
| S570/42-500 | S570 | AVK | DN500 Resilient Seated Gate Valve With DN100&DN150 Bypass | Resilient Seated Gate Valve | DN 500 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange Bypass | 30 Apr 2020 |
| S570/42-600 | S570 | AVK | DN600 Resilient Seated Gate Valve With DN100&DN150 Bypass valve | Resilient Seated Gate Valve | DN 600 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange Bypass | 4 May 2020 |
| S570/42-750 | S570 | AVK | DN750 Resilient Seated Gate Valve With DN150 Bypass | Resilient Seated Gate Valve | DN 750 | 16 | 40°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange Bypass | 1 Oct 2020 |
| S570/92-450 | S570 | AVK | DN450 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 450 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 30 Apr 2020 |
| S570/92-500 | S570 | AVK | DN500 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 500 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 30 Apr 2020 |
| S570/92-600 | S570 | AVK | DN600 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 600 | 16 | 70°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 30 Apr 2020 |
| S570/92-750 | S570 | AVK | DN750 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 750 | 16 | 40°C | Ductile Cast Iron | Polymeric to AS 4158 | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC | Flange x Flange | 1 Oct 2020 |

End of Record

Licence No: SMK02420

Issued Date: 23 January 2021

This schedule supersedes all previously issued schedules



* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.